What is claimed is:

 A polyolefin resin molding composite comprising a surface layer and a foam layer, or a surface layer, a foam layer, and a base member,

the foam layer being produced by fusion bonding thermoplastic expanded resin particles one another by molding, the thermoplastic expanded resin particles comprising a core that is made of a crystalline thermoplastic resin and is in an expanded state and a polyethylene resin coat covering the core, and

the surface layer comprising a thermoplastic synthetic resin having a melting point of 5°C or more higher than a melting point of polyethylene resin constituting the coat of the particles.

- A polyolefin resin molding composite according to claim
 wherein the polyethylene resin coat covering the core is in a substantially non-expanded state.
- 3. A polyolefin resin molding composite according to claim 2, wherein the polyethylene resin coat contains an ethylene polymer having a melting point lower than the crystalline thermoplastic resin constituting the core, or an ethylene polymer that substantially exhibits no melting point.
- 4. A polyolefin resin molding composite according to claim 3, wherein compressive hardness of the foam layer is 0.05 to 0.7 MPa.
 - 5. A polyolefin resin molding composite according to claim

- 4, wherein void fraction of the foam layer is 1 to 40%.
- 6. A polyolefin resin molding composite according to claim 3, wherein the thermoplastic synthetic resin constituting surface layer is a polyolefin resin.
- 7. A polyolefin resin molding composite according to claim 6, wherein compressive hardness of the foam layer is 0.05 to 0.7 MPa.
- 8. A polyolefin resin molding composite according to claim 7, wherein void fraction of the foam layer is 1 to 40%.